

Wide-Area Protection and Control Scheme Maintains Central America's Power System Stability


José Vicente Espinoza
AMM-Guatemala

Armando Guzmán, Fernando Calero,
Mangapathirao V. Mynam, and Eduardo Palma
Schweitzer Engineering Laboratories, Inc.


230 kV Backbone Connects Countries From Guatemala to Panama



Guatemala Wheels Power From Mexico to Central America



Unstable Oscillation Separates Guatemala From Rest of Central America




Synchrophasor System Details

- 23 PMCUs (30 message/sec)
- Leased communications network
- Synchrophasor processing units (SPUs)
- Software PDC at control center
- System visualization and analytics

Synchrophasors and Traditional SCADA



Normal Operational Experience




Not possible with 4 second asynchronous SCADA rate


Event Happens After Synchronization




Wide-Area Prot. Scheme Architecture




PMcus Receive Control Commands and Provide Synchronized Measurements



Protection Scheme Trips Interconnection to El Salvador



Scheme 1 – Synchronized Power




Synchronized Power Levels

Total Power (AGU+MOY)	Delay (ms)
200	1200
245	600
297	300


Scheme 2 – Modal Analysis

- Central American interconnection shows possible 0.17 Hz unstable mode
- 20-second observation window
- 2 bands are defined
 - ◆ 0.1 to 0.3 Hz unstable band
 - ◆ 0.5 to 0.9 Hz steady-state oscillations

Real-Time Modal Analysis Detects Unstable Oscillations



Signal Estimation Using Modal Analysis



Damping Ratio and SNR

Damping Ratio

$$\zeta_m = - \frac{\sigma_m}{\sqrt{\sigma_m^2 + (2\pi f_m)^2}}$$

σ_m Damping constant

f_m Oscillation frequency

Signal to Noise Ratio

$$SNR = 10 \log \left(\frac{\sum_{n=0}^N y[n]^2}{\sum_{n=0}^N (\hat{y}[n] - y[n])^2} \right)$$

P_{TOT} —

Modal Analysis

If $SNR > SNR_{THRE}$
Identify Mode
 $0.1 \text{ Hz} < f_m < 0.3 \text{ Hz}$

$A_m(k)$ $\zeta_m(k)$
$A_m(k-1)$ $\zeta_m(k-1)$
$A_m(k-2)$ $\zeta_m(k-2)$

$A_m(k) > A_m(k-1) > A_m(k-2) > A_{thre}$
 $\zeta(k) < \zeta(k-1) < \zeta(k-2) < \zeta_{thre}$

Activate Alarms
and Trips


Real-Time Modal Analysis Decision Logic

- Signal-to-Noise Ratio (SNR)
- Mode Frequency (f_m)
- Mode Amplitude (ζ_m)
- Mode Damping Ratio (A_m)


MA Scheme Mitigates Unstable Oscillation – July 28, 2012

- MA scheme enabled in mid-June 2012
- Unstable mode appears after synchronizing two parts of Central American power system

MA Scheme Mitigates Unstable Oscillation – July 28, 2012




Synchrophasor-Based Control Successfully Stabilizes System



Guatemala Remains Stable

- Guatemala reaches new steady state
- Mexican power system largely contributes



Additional Operations of System

- Several scheme operations in July and August 2012
- Four operations in a single day, August 12, 2012
- Central America has maintained stability for all scheme operations

Questions?